

## Applications

- Stream Gaging
- Flood Warning
- Discharge Monitoring
- Watershed Monitoring
- Water Quality Monitoring
- Nutrient Monitoring
- Lake/Reservoir Monitoring
- Tide Monitoring
- Groundwater Monitoring
- Meteorological Observation



## Logger/Transmitter

With optional cellular and Iridium communications

**Cost-effective way to measure, log, calculate, and transmit data from remote locations**

**32 independent measurements with 1,000,000 readings of most hydrological, meteorological, environmental or related sensors**

**Built-in support for all meteorological satellites including GOES, EUMETSAT, INSAT, and MTSAT to operate anywhere**

**Improved analog accuracy and high resolution analog channels with support for 2 additional plug and play modems**

**Wi-Fi for operation with wireless devices, including smart phones, tablets, and PCs**

### Compact multi-communication logger

Built-in SDI-12, Analog, Digital, RS485 and 4-20mA measurement circuitry with lightning protection. Two independent SDI-12 inputs/ports increases the flexibility of SDI sensor scheduling with up to 2 additional slots for modems and up to 3 built-in slots for GOES transmitter and 2 redundancies..

### Adaptable over time

Allows for support of rapidly changing communications standards, preventing hardware obsolescence.

### Simple and intuitive software

Use with LinkComm interface for intuitive programming with the Android, iPhone, PC, and Mac. The SatLink 3 can also be paired with Hydromet Cloud for data collection, retrieval, and viewing via the web.

### Python scripting

Application specific behaviors and extended connectivity beyond standard sensor configurations and data formats with Python scripting.

# Technical Specifications

## Feature

### GENERAL INFORMATION

SIZE	6.06 in. x 9.24 in. x 2 in.
WEIGHT	3.1 lbs (1.42kg)
IP RATING	IP63 (with NEMA enclosure)
OPERATING TEMPERATURE	-40° C to +70° C

### POWER REQUIREMENTS

VOLTAGE	9-20 VDC
QUIESCENT	< 2 mA typ @12.5 VDC

### SDI-12

INDEPENDENT CHANNELS	2
COMPLIANCE	V1.3 logger
POWER	500mA max

### ANALOG - SINGLE ENDED

NUMBER OF INPUTS	2
RANGE*	0-5V
ACCURACY @ 25°C	0.004% typ
RESOLUTION	0.298 $\mu$ V

### ANALOG - DIFFERENTIAL

NUMBER OF INPUTS	3
RANGE*	$\pm 39$ mV, $\pm 312$ mV, $\pm 2.5$ V
ACCURACY @ 25°C	0.004% typ
RESOLUTION	0.298 $\mu$ V @ $\pm 2.5$ V scale

### ANALOG - 4-20MA

NUMBER OF INPUTS	1
RANGE	0-22mA
ACCURACY @ 25°C	0.02%
LOAD	Internal 200 $\Omega$

### DIGITAL - INPUTS/OUTPUTS

NUMBER OF INPUTS	2, 0-15 V, optional low level input
INPUT TYPE	Status, counter, frequency
MAX INPUT FREQUENCY	10KHz, optional debouncing, internal pull
NUMBER OF OUTPUTS	2
OUTPUT TYPES	On/off/pulse Open collector w/100 ohm limiting resistor. 100mA, 15V max

### OTHER I/OS & CONNECTIONS

PRECISION ANALOG REFERENCE	2.5V 10.0 mA
SWITCH 12V	1.0 A (2 available)
PROTECTED 12V	1.0 A
RS485	
GPS INPUT	SMA-F
RS232	DB9
USB (OTG)	USB MICRO AB
USB HOST	Type A
microSD	Internal, Expandable Up to 32 GB

### RF POWER OUTPUT AND TX FREQUENCY

RF OUTPUT POWER	1.25-14 Watts depending on settings
RF TRANSMIT FREQUENCY	401.63 MHz to 402.85 MHz (depending on satellite type and channel assignment)

**CE** COMPLIANT

NOTE: In humid/hostile environments we RECOMMEND installing SatLink in a NEMA 4 enclosure. Sutron also recommends adding a lightning protection module such as the Sutron 8111-1113-1 for remote systems.

\*Nominal. Guaranteed Analog Input Range Over Temperature Is 0-4.98 V,  $\pm 2.49$  V,  $\pm 311$  mV,  $\pm 38.9$  mV.

