



Automatic Cleaning Module (ACM) For TU5300sc/TU5400sc

The ACM ensures your TU5 sample vial is free of contamination that may interfere with your low-level turbidity measurements. Let Hach Service keep your ACM maintained properly and on schedule to avoid measurement errors and the need for manual cleaning.

Benefits of Service

- Ensures peak performance to protect TU5 turbidity measurements against vial contamination
- Detects and prevents issues that can degrade performance or reduce instrument life
- Eliminates time and hassle of performing service and managing maintenance schedules
- Technical support hotline provides rapid and direct resolution and field support when an immediate fix is not possible

Annual Average Maintenance Time: Up to 1 hour Recommended Maintenance Frequency: 1x / year

Essential Maintenance Tasks Performed

Routine:

- Perform visual inspection
- Clean device exterior
- Replace wiper to ensure optimal cleaning

Advanced:

- Replace wiper shaft to maximise instrument uptime
- Verify and ensure proper operation
- Resolve any error or warning messages that may impact functionality
- Produce service report and performance certificate

Parts Replaced During Maintenance			
Part #	Description	Qty.	Frequency
LZY915 LZQ176	Silicone wiper or Fibre wiper	1	12 months
LZQ160	Wiper shaft	1	36 months

These parts and replacement labour are included with a Hach Service Plan at the recommended frequency as long as the plan is renewed. Service Plan for the ACM is sold only in combination with the associated TU5300sc/TU5400sc Service Plan. Coverage is available for repairs on site or at the Hach Service Centre.

For more information, visit: **www.uk.hach.com/service**